

## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

### 1. Identification of the substance or mixture and of the company

#### 1.1. Product identifier

Name of substance / trade name: RustPrimer

#### 1.2. Relevant identified uses of the substance or mixture and use advised against

Relevant identified uses: primer  
Recommended restriction of application: RustPrimer is a primer for medium corrosion protection.

#### Details of the supplier that provides the safety data sheet

##### Manufacturer / supplier

Company: SICC Coatings GmbH  
Wackenbergstraße 78-82  
D-13156 Berlin, Germany  
Phone: +49 (0) 30 / 500196-0  
Fax: +49 (0) 30 / 500196-20  
E-mail address: [info@sicc.de](mailto:info@sicc.de)  
Responsible/  
Exhibitor: application engineering / research and development

1.3. Emergency number out of normal business hours 112  
(Mon-Fri 8:00 – 16.30 pm)

### 2. Possible hazards

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008  
No hazardous substance or mixture.

#### 2.2. Label elements

Labeling elements according to Regulation (EC) No 1272/2008  
No hazardous substance or mixture.

##### Safety instructions:

P101: If medical advice is required, provide packaging or labeling label  
P102: Keep out of the reach of children.  
P103: Read label before use.

##### Other marking elements

EUH208: Contains 2-butanone oxime. Can cause allergic reactions.  
EUH210: Safety data sheet available on request.

#### 2.3. Other hazards

Based on the available information, the product does not contain any PBT or vPvB substances in concentrations greater than 0.1%.

## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

### 3. Composition / information on ingredients

3.1. **Substance** not applicable

3.2. **mixtures**

**2-butanone oxime (0,5 %)**

CAS number: 96-29-7

Acute Tox. 4 (Acute toxicity dermal, category 4, H312)

Eye Dam. 1 (Severe eye damage/irritation, Category 1, H318)

Skin Sens. 1 (sensitization of the skin, category 1, H317)

Carc. 2 (carcinogenicity, category 2, H351)

**Dowanol DPnB (2,0 %)**

CAS number: 142-96-1

Flam. Liq. 3 (Flammable liquids, category 3, H226)

Skin irritation. 2 (corrosive/irritant effect on the skin, category 2, H315)

Eye Irrit. 2 (Severe eye damage/ irritation, Category 2, H319)

STOT SE 3 (Specific target organ toxicity (single exposure): respiratory irritation, category 3, H335)

Aquatic Chronic 3 (hazardous to waters: chronic, category 3, H412)

### 4. First aid measures

4.1. **Description of the first aid measure**

General information	No special first aid measures required. Take affected persons out of danger. First aid must protect itself.
After inhalation	for complaints - fresh air supply
After skin contact	wash skin with soap and water
After eye contact,	remove contact lenses, keep eyelids open and rinse with plenty of water, seek medical advice
After swallowing	may cause nausea, vomiting and diarrhea, also gastrointestinal irritation; call Physician and name the substance.

4.2. **Most important symptoms and effects, both acute and delayed**

Symptoms:	no information available
Risks:	no information available

4.3. **Indication of any immediate medical attention and special treatment needed**

Treatment:	no information available
------------	--------------------------

### 5. Fire fighting measures

5.1. **Extinguishing media**

suitable:	foam, carbon dioxide, dry chemicals, spray mist, water
Not suitable for safety reasons:	Observe local conditions.

5.2. **Special hazards arising from the mixture**

Contained containers may burst during extreme heat (pressure build-up), smoke, carbon dioxide

5.3. **Instructions for firefighting**

Avoid contact with skin. Keep container tightly closed. Material is not combustible if moisture is contained.

## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

protective equipment / see chapter 2-5

#### 6.2. Environmental precautions

Observe local, governmental regulations; Not in the keep the sewage system away.

#### 6.3. Methods and materials for retention and cleaning

Dispose of materials with non-combustible absorbents (eg sand, sawdust, etc.) and dispose of according to local regulations. Clean with water and detergents, preferably do not use solvents.

#### 6.4. Reference to other sections

See section 7, 8 and 13 of the MSDS for further information Safety Data Sheet

### 7. Handling und storage

#### 7.1. Precautions for safe handling

Advice on safe handling

Observe the minimum standards for the TRGS 500 (Technical rule for hazardous substances). Avoid contact with eyes and skin.

Measurement for protection against fire and explosions

The product is not combustible if moisture is still present. Hazardous containers must be cooled with water.

#### 7.2. Conditions for safe storage, including enviromental compatibility

Information to storage conditions

store in a cool, frost-free place

Requirements to be met by storerooms and containers

Keep container closed, protect from freezing and heat, do not empty container with pressure, no pressure containers

Storage class:

12 – non-flammable liquids

#### 7.3. Spezific end use

RustPrimer is a watery anticorrosion primer for internal and exterior use on basis of acrylic resin.

Gis-Code BSW20

Technical information of manufacturer must be observed.

### 8. Exposure controls / personal protection equipment

#### 8.1. Parameters to be monitored

**Occupational exposure limits and / or biological limits workplace exposure limits (AGW) Germany**

No substances to be monitored.

#### 8.2. Limitation and monitoring of exposure

Technical measures and applications of appropriate work procedures, as listed in Section 7, shall prevail over the use of personal protective equipment. Recommended analytical procedures for workplace measurements: see the Federal Institute for Occupational Safety and Health (BauA).

**Personal protective equipment:**

Respiratory protection

no special protective equipment required

Exceeding the occupational exposure limit values, a suitable respiratory protective device must be worn. If there are no occupational exposure limits, sufficient respiratory protection measures should be taken when aerosol and

## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

### Skin /Hand protection

mist are formed. Recommended: filter against organic vapors (type A), filter against organic vapors (type AX)

Wear suitable gloves according to EU Directive 89/686 / CEE. Observe the manufacturer's instructions regarding permeability and breakthrough time as well as the special conditions at the workplace (mechanical load, contact duration). Protective gloves should be replaced at the first time of wear.

Material nitrile gloves

Breakthrough time > = 8 h

Glove thickness 0.4 mm

### Eye / face protection

Safety glasses with side protection (DIN EN 166)

### Body protection

Chemically custom work clothing adapted to the workplace and sturdy shoes.

### General protective and hygienic measures:

Keep away from food, drink and animal feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / vapors / aerosols. Avoid contact with eyes and skin. Do not eat and drink while working.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form:	liquid	
Color:	RAL light grey 7035	
Odor:	characteristic	
Odor threshold:	n.d.	
Vapor pressure:	n.d.	
pH value:	9.00 ± 0.2 at 20 °C	DIN 19266
Melting point / freezing point:	0 °C water = 0 °C	
Initial boiling point:	100 °C water = 100 °C	
Flash point:	<60 °C	
Evaporation rate:	n.d.	
Flammability:	n.a.	
Upper explosion limit:	n.a.	
Lower explosion limit:	n.a.	
Oxidizing properties:	n.a.	
Density:	1.4 kg/dm <sup>3</sup>	DIN EN ISO 2811-1
Vapor density (20 °C):	n.b.	
Auto-ignition:	n.a.	
Partition coefficient n-octanol / water:	n.b.	
Decomposition temperature:	n.d.	
Explosive properties:	n.a.	
Viscosity:	85 ± 2 KU	
* N.a. = not applicable		
* N.d. = not determined		

### 9.2. Other information

none

## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

### 10. Stability and reactivity

10.1. Reactivity	No decomposition if used according to specifications application
10.2. Chemical stability	No decomposition if used according to specifications application
10.3. Possibility of hazardous reactions	No decomposition if used according to specifications application
10.4. Conditions to avoid	See chapter 7
10.5. Incompatible materials	Avoid contact with strong acids, strong alkalis
10.6. Hazardous decomposition products	No decomposition if used according to specifications application. Fire, also heating by welding and cutting produces smoke, carbon dioxide and carbon monoxide.

### 11. Toxicological information

#### 11.1. Information on toxicological effects

Information on toxicological effects

##### a) Acute toxicity

Components which may contribute to acute oral toxicity:

There are no relevant ingredients in the mixture.

The mixture is not classified as Acute Oral Toxicity.

Ingredients which may contribute to acute dermal toxicity

no relevant ingredient

The mixture is therefore not classified as Acute Toxicity dermal.

Components which may contribute to acute inhalation toxicity

There are no relevant ingredients in the mixture.

The mixture is not classified as Acute toxicity by inhalation.

##### b) Corrosive/irritant effect on the skin

Relevant ingredients:

Dowanol DPnB (2.0 %), classification of the substance: category 2, was considered additive.

The general limits (GCL) must be observed: Category 2: 10 %

##### c) Severe eye damage/irritation

Relevant ingredients:

2-butanone oxime (0,5 %), classification of the substance: category 1, was considered as additive.

The general limits (GCL) must be observed: Category 1: 3 % Category 2: 1

Dowanol DPnB (2,0 %), classification of the substance: category 2, was considered as additive.

The general limits (GCL) must be observed: category 2: 10 %

##### d) Respiratory tract/skin sensitisation

Ingredients which may contribute to respiratory sensitisation:

There are no relevant ingredients in the mixture.

The mixture is not classified as respiratory sensitisation.

Ingredients which may contribute to skin sensitisation:

Relevant ingredients:

2-butanone oxime (0,5 %), classification of the substance: category 1

The general limit values (GCL) must be observed: Category 1: 1 %

The mixture is not skin sensitizing. Nevertheless, allergies can be triggered in sensitive persons.

##### e) Germ cell mutagenicity

There are no relevant ingredients in the mixture.

## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

The mixture is not classified in germ cell mutagenicity.

### **f) Carcinogenicity**

There are no relevant ingredients in the mixture.

The mixture is not classified in this hazard category.

### **g) Toxicity for reproduction**

Components that may contribute to reproductive toxicity:

There are no relevant ingredients in the mixture.

The mixture is not classified as toxic to reproduction.

Ingredients which may contribute to lactation effects:

There are no relevant ingredients in the mixture.

The mixture is not classified in the additive category for effects on lactation.

### **h) Specific target organ toxicity at single exposure**

Components that may contribute to specific target organ toxicity (single exposure):

There are no relevant ingredients in the mixture.

The mixture is not classified in Specific Target Organ Toxicity (single exposure).

Components that may contribute to Specific Target Organ Toxicity (single exposure): Respiratory irritation:

Relevant ingredients:

Dowanol DPnB (2,0 %), classification of the substance: Category 3

Substance Specific Limit Values (SCL): Category 3: 10

The mixture is classified as Specific Target Organ Toxicity (single exposure): Respiratory Irritation not classified.

Components that may contribute to Specific Target Organ Toxicity (single exposure): Anesthetic effect:

There are no relevant ingredients in the mixture.

The mixture is classified as Specific Target Organ Toxicity (single exposure): No narcotic effect.

### **i) Specific target organ toxicity on repeated exposure**

There are no relevant ingredients in the mixture.

The mixture is not classified in Specific Target Organ Toxicity (repeated exposure).

### **j) Aspiration hazard**

There are no relevant ingredients in the mixture.

The mixture is not classified as an aspiration hazard.

## 12. Ecological information

### 12.1. Toxicity

Components that may contribute to acute water hazard:

There are no relevant ingredients in the mixture.

The mixture is classified as Hazardous to the aquatic environment: Acute Not classified.

Components that may contribute to chronic water pollution.

Relevant ingredients:

Dowanol DPnB (2.0%, Category 3).

The limit value must be observed: Category 3: 25 %, Category 4: 25 %.

The mixture is not classified in this hazard category.

Ingredients that may contribute to ozone layer depletion.

There are no relevant ingredients in the mixture.

The mixture is not classified in The ozone layer depleting.

### 12.2. Persistence and degradability

Components that may contribute to the persistent, bioaccumulative, and toxic properties (PBT) of the mixture:

No relevant components

Components that may contribute to the very persistent and very bioaccumulative properties (vPvB) of the mixture:

No relevant components

Components that may contribute to persistent, mobile, and toxic properties (PMT) of the mixture:

## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

No relevant component

Components that may contribute to very persistent and very mobile properties (vPvM) of the mixture:

No relevant component

### 12.3. Bioaccumulative

There are no data available on the product

### 12.4. Mobility in the ground

There are no data available on the product

### 12.5. Result of the PTB and vPvB assessment

There are no data available on the product

### 12.6. Endocrine disrupting properties

There are no data available on the product

### 12.7. Other adverse effects

There are no data available on the product

## 13. Disposal considerations

### 13.1. Waste treatment methods

Dispose of in accordance with local regulations.

Regular disposal by incineration in a combustion plant, local and official regulations must be observed.

Treatment of contaminated packaging

Packaging must be disposed of in a completely emptied state (drip-free, non-wiping and free of spatula). Packaging should be reused or recycled, in compliance with the applicable local and governmental regulations.

**Waste key according to Ordinance on Waste Disposal (AVV)**

080120 aqueous suspensions containing paints or varnishes

## 14. Transport information

### 14.1. UN number

The product is not a dangerous good in national / international road, rail, sea, and air transport.

### 14.2. UN proper shipping name

ADR / RID

The product is not a dangerous good in national / international road, rail, sea, and air transport.

**IMDG code / ICAO-TI / IATA-DGR**

The product is not a dangerous good in national / international road, rail, sea, and air transport.

### 14.3. Transport hazard class

The product is not a dangerous good in national / international road, rail, sea, and air transport.

### 14.4. packaging group

The product is not a dangerous good in national / international road, rail, sea, and air transport.

### 14.5. environmental hazards

The product is not a dangerous good in national / international road, rail, sea, and air transport.

### 14.6. Special precautions for the user

The product is not a dangerous good in national / international road, rail, sea, and air transport.

### 14.7. Transport in bulk according to Annex II of the MARPOL Convention and the IBC Code

The product is not a dangerous good in national / international road, rail, sea, and air transport.



## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

### 15. Regulatory

#### 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

##### EU-regulations

Regulation (EC) No 1005/2009 (substances that deplete the ozone layer):

Not applicable

Regulation (EC) No 850/2004 (persistent organic pollutants):

Not applicable

Regulation No 649/2012 (export and import of dangerous chemicals):

Not applicable

Regulation (EC) No 648/2004 (Detergents Regulation):

Not applicable

Authorization in accordance with Title VII of Regulation (EC) No 1907/2006:

No

Restrictions under Title VIII of Regulation (EC) No 1907/2006:

No

National regulations, e.g.

Water hazard class      WGK 1 Self-leveling according to VwVws (regulation of water-endangering substances)

Solvent regulation:      Wb < 30 g/l (maximum value according to VOC Annex II A/i 140 g/l)

#### 15.2. Chemical Safety Assessment

No substance safety assessment has been carried out by the manufacturer for this mixture.

### 16. Additional information

#### Changes to the last version

Replaced datasheet from 22.08.2023

#### Literature and data sources

REACH Regulation (EC) No 1907/2006, as last amended by Regulation (EU) 2017/1000

CLP Regulation (EC) No 1272/2008, as last amended by Regulation (EU) 2017/776

#### Internet

<http://www.baua.de>

<http://publikationen.dguv.de>

<http://dguv.de/ifa/stoffdatenbank>

<http://www.gischem.de>

<http://echa.europa.eu/en/candidate-list-table>

#### Methods according to Article 9 of Regulation (EC) No 1272/2008 on the evaluation of the information for classification.

The hazard characteristics of the product have been assessed in accordance with Annex I to Regulation (EC) No 1272/2008 (CLP Regulation).

Text of the dangers and / or safety instructions referred to in section 2

EUH208: Contains 2-butanone oxime. Can cause allergic reactions.

EUH210: Safety data sheet available on request.

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of the reach of children.

P103: Read label before use



## MATERIAL SAFETY DATA SHEET **RustPrimer**

According to regulation (EC) 1907/2006

created: 14.07.2020

revised 13.11.2025

### **Data stand area:**

Application Technology Phone +49 (0) 30 / 500196-0

### **Further information**

Rejection of liability: We have obtained the information contained in this SDS from sources which we consider to be reliable. The correctness of the information, in printed form, is not guaranteed. The conditions or methods of handling, storage, use or disposal of the product are beyond our control, and possibly also outside our information area. For these and other reasons, we accept no responsibility and expressly disclaim liability for loss, damage or expense that may result from the handling, storage, use or disposal of the product, or in any way connected to it. This MSDS has been developed for this product and should only be used with it.

This information describes the safety requirements of the product (s) and is based on the present state of our knowledge. They do not constitute a guarantee for the properties of the product (s) described in the sense of the statutory warranty regulations. For the properties of the product, please refer to the relevant product leaflet.

Commodity number / customs tariff number: 32091000